

In the claims:

1. (currently amended) A method for transmission-end preparation of source-coded audio data of at least one useful signal source (1), in particular for transmission via AM channels of a predetermined broadcast channel raster, ~~with the following features: comprising the steps of~~

- separating the source-coded audio data of at least one useful signal source (1) ~~are separated (2)~~ into a main data stream (HD) and at least one auxiliary data stream (ZD), where the main data stream (HD) contains at least the amount of information that is required for a comprehensible reproduction of at least one useful signal source (1) and the auxiliary data stream (ZD) contains information for quality improvement,

- modulating the main- and auxiliary data streams (HD, ZD) ~~are modulated and accommodated~~ accomodating in respective different channels (K1, K2) of the predetermined broadcast channel raster, and

- incorporating a signaling into the main data stream (HD) on the transmitter end, which indicates whether an auxiliary data stream (ZD) is provided for the same useful signal source (1) and in what channel it is provided.

2. (currently amended) A method for receiver-end preparation of audio data, which are contained in main- and auxiliary data streams (HD, ZD), in particular for transmission via AM channels of a predetermined broadcast channel raster, where mutually associated main- and auxiliary data streams (HD,

ZD) each originate from at least one useful signal source (1) and the mutually associated main- and auxiliary data streams are accommodated in respective different channels (K1, K2) of the predetermined broadcast channel raster, ~~including the following steps:—comprising the steps of~~

- using a receiver (4) with a low reproduction quality ~~is used~~ to demodulate and decode only the main data stream (HD),

- intentionally using a receiver (7) with higher reproduction quality ~~is intentionally used~~ to demodulate and decode only the main data stream (HD) or the main data stream (HD), and

- demodulating and decoding at least one associated auxiliary data stream (ZD) ~~are demodulated and decoded~~, where mutually associated demodulated and decoded data streams are linked to one another in such a way that an increase is achieved in the reproduction quality for the at least one useful data source (1), and

- incorporating ~~decorating~~ a signaling into the main data stream (HD) on the transmitter end, which indicates whether an auxiliary data stream (ZD) is provided for the same useful signal source (1) and in what channel it is provided.

Claim 3 cancelled.

4. (currently amended) The method according to claim 1, ~~characterized in that~~ further incorporating additional information ~~is incorporated~~ into an auxiliary data stream (HD), which indicates what information the auxiliary data stream

contains and optionally, how the main data stream (HD) is to be combined on the receiver end with the at least one associated auxiliary data stream (ZD).

5. (currently amended) The method according to claim 2, ~~characterized in that~~further comprising executing the linkage of the associated main data- and auxiliary data streams ~~is executed~~ in accordance with at least one of the following criteria:

- to reduce the amount of coding artifacts,
- to increase bandwidth for the reproduction of audio data,
- to generate a stereo signal.

6. (currently amended) The method according to claim 1, ~~characterized in that~~further comprising using the scalability of MPEG 4 data streams ~~is used~~ to separate the source-coded audio data of the useful signal source (1) into the main data stream (HD) and at least one auxiliary data stream (ZD).

7. (currently amended) A transmitter for the preparation of source-coded audio data from at least one useful signal source (1), in particular for transmission via AM channels of a predetermined broadcast channel raster, with ~~the following features: comprising~~

- a separation device (2) for the audio data of a useful signal source (1) into a main data stream (HD) and at least one associated auxiliary data stream (ZD),

- a modulation unit (3) modulating the main- and auxiliary data streams, where this modulation unit (3) can in particular be supplied with carrier signals in such a way that mutually associated main- and auxiliary data streams can be transmitted in respective different channels of a predetermined broadcast channel raster, and

- means for incorporating a signaling into the main data stream (HD) on the transmitter end, which indicates whether an auxiliary data stream (ZD) is provided for the same useful signal source (1) and in what channel it is provided.

8. (Currently a mended) A receiver for receiver-end preparation of source-coded audio data, which are accommodated in main- and auxiliary data streams, in particular for transmission via AM channels of a predetermined broadcast channel raster, with the following features: comprising

- a demodulation unit (5,8) and decoding unit (6,9) for at least main data streams (HD),

- an evaluation unit (10) for a signaling and optional additional information, where the signaling indicates which channel contains an auxiliary data stream (ZD) associated with a main data stream (HD) and the optionally provided additional information indicate what information the auxiliary data stream (ZD) contains and how the main data stream (HD) is to be combined with the at least one auxiliary data stream (ZD) on the receiver end,

- a linkage unit (8) for mutually associated main- and auxiliary data streams, which can be controlled by the evaluation unit (10), and

- means for incorporating a signaling into the main data stream (HD) on the transmitter end, which indicates whether an auxiliary data stream (ZD) is provided for the same useful signal source (1) and in what channel it is provided.